

Bulkhead

14W 1100Lm 3000K 4000K 6000K

Item: 1002254 (14W 6000K On/Off Sensor)
 Item: 1002253 (14W 3000K EPS)
 Item: 1002252 (14W 3000K Dim Sensor)
 Item: 1002251 (14W 3000K)




Barrier

LED Flatlight: If you compare our LED Products to traditional lighting you will see that our lighting radiates less heat and has a much longer life span and a very low maintenance cost. Our products are made of quality parts and have a high energy saving level. We think quality is very important so we always make sure our products are tested and have the right certificates.

Applications: Office, school, Hospital, Retail shops, Hotel, Workshop

Wattage	14W
Luminous Flux	3000K: 1100Lm 6000K: 1300Lm
Kelvin	3000K 6000K (4000K Optional)
Colour Rendering Index	>80
Beam angle	120°
UGR	<16
Power Factor	>0.5
Voltage / Current	220-240V 50~60Hz
Driver	Tridonic
IP-Code	IP66 IK08 and 850 GWT requirement
Sensor on/off	Optional
Dim Sensor	Optional (MERRYTEK driver)
EPS	Optional (2W 90min work time)
material	White/Black Plastic with Opal PC
Dimensions	Ø301 x H 95mm
Operation Temperature	-20 + 45°C
Lifetime	50.000h
Warranty	3 Years (Optional 5)
Certification	CE, RoHS



All transactions with LED Flatlight BV are subject to our general terms of trading, Copies are on request. All specifications are subject to change without notice.