

## Downlight

1001808 Downlight 'Level' 20W 3000K 36° Ø120mm  
 1001807 Downlight 'Level' 28W 3000K 40° Ø150mm





# Level II



LED Flatlight: If you compare our LED Products to traditional lighting you will see that our lighting radiates less heat and has a much longer life span and a very low maintenance cost. Our products are made of quality parts and have a high energy saving level. We think quality is very important so we always make sure our products are tested and have the right certificates.

Applications: Residential areas, Corridor, Technical area, Restroom, Parking area, Office rooms

Wattage	20/28W
Luminous Flux	2300Lm (3000K 20W) 2455Lm (4000K 20W) 3120Lm (3000K 28W) 3325Lm (4000K 28W)
Kelvin	3000/4000K
Colour Rendering Index	>80 (90 optional)
Beam angle	15/24/40°
Driver	On board
Power Factor	>0,9
Voltage / Current	220-240V 50~60Hz
IP-Code	IP20
Dimmable	No
Housing Material	Aluminum White
Dimensions	Ø160 x 99 x 144.87 mm
Working temperature	-20 + 45°C
Lifetime	50.000h
Warranty	3 Years
Certification	CE, RoHS



All transactions with LED Flatlight BV are subject to our general terms of trading, Copies are on request. All specifications are subject to change without notice.