

## Streetlight

75-420Watt 140Lm/w and 170Lm/w optional  
 300W + 420W: 145Lm/w



# Sokom



LED Flatlight: If you compare our LED Products to traditional lighting you will see that our lighting radiates less heat and has a much longer life span and a very low maintenance cost. Our products are made of quality parts and have a high energy saving level. We think quality is very important so we always make sure our products are tested and have the right certificates.

Applications: Street, Parking

Luminous Efficacy	75W, 115W, 145W, 180W, 200W: 140lm/w and 170lm/w optional 300W, 420W: 145lm/w
Color Temperature	3000K, 4000K, 5000K, 5700K, 6500K
Power Consumption	75W, 115W, 145W, 180W, 200W, 300W, 420W
CRI (Color Accuracy)	Ra>70 Ra>80
Replaces (Comparable to)	75W: 300W PSMH (140lm/w) and 400W PSMH (170lm/w) 115W: 450W PSMH (140lm/w) and 500W PSMH (170lm/w) 145W: 550W PSMH (140lm/w) and 700W PSMH (170lm/w) 180W: 700W PSMH (140lm/w) and 800W PSMH (170lm/w) 200W: 800W PSMH (140lm/w) and 1000W PSMH (170lm/w) 300W: 1000W PSMH (145lm/w) 420W: 1200W PSMH (145lm/w)
Dimensions/Colour	75W/115W/145W: 24*11*3", 60*27*7.8 (cm.) Black 180W/200W: 27*14*3", 69.4*35*7.8 (cm.) (cm.) Black 300W: 29*14*3", 73.9*30.6*7.5(cm.) Silver 420W: 30*14*3", 74*36*7.5 (cm.) Silver
Beam angle	125°
Shipping Weight	75W/115W/145W: 13 (lbs.) 180W/200W: 15 (lbs.) 300W: 23 (lbs.) 420W: 16.53 (lbs.)
Lifespan	estimated > 50,000 hours of maintenance-free operation to L70 at 25°C (77°F)
Input Voltage	100-277VAC/277-480VAC
IP&IK	IP66 IK08
Warranty	5 Years
Certification	UL/cUL, DLC



All transactions with LED Flatlight BV are subject to our general terms of trading, Copies are on request. All specifications are subject to change without notice.