

HCL Proof Highbay
 100/150/200W

HCL Proof



LED Highbay to replace the traditional HPS, Metal Halide & Mercury Vapor Highbay with an energy saving of over 70%. Using high quality parts for long lifetime. Easy on/off switching and optional dimming. Stay longer efficient because of the less heat production, the optics stay more clean. Various beamangle and Kelvin colors available.

Applications: Warehouse, Logistic center, production plant, Exhibition hall, Gym, Store

Wattage	100/150/200W
Kelvin	5000K
Luminous Flux	100W: 12000Lm 150W: 18000Lm 200W: 24000Lm
Colour Rendering Index	Ra>75
Light Source	Osram
Beam Angle	60°/90°
Driver	Inventronics/Meanwell
Dimmable	No
Power Factor	>0,95
Voltage/ current	AC200~240V (Europe) AC100~277V (USA)
IP-code	IP67
Housing Material	Extruded aluminium + PC
Operation Temperature	-40~+50°C
Dimensions	100W: 356x260x155mm 150W: 356x260x155mm 200W: 356x340x155mm
Lifetime	50.000 hours
Warranty	3 years
Certification	CE, RoHS, TUV, CB, FCC, UL, DLC



All transactions with LED Flatlight BV are subject to our general terms of trading, Copies are on request. All specifications are subject to change without notice.