LED FLATLIGHT
ZILVERENBERG 37A
5234 GL 's-Hertogenbosch
(0)73 6 89 57 99
The Netherlands

LED Highbay
70/90/100/120/150/200/240/300
(Optional: sensor)

Titan

LED Highbay to replace the traditional HPS, Metal Halide & Mercury Vapor Highbay with an energy saving of over 70%. Using high quality parts for long lifetime. Easy on/off switching and optional dimming. Stay longer efficient because of the less heat production, the optics stay more clean. Various beamangle and Kelvin colors available.

Applications: Warehouse, Logistic center, production plant, Exhibition hall, Gym, Store

Wattage	70/90/100/120/150/200/240/300W
Kelvin	3000/4000/5000K
Luminous Flux	70W: 9800Lm 140Lm/W Ø264 x 172,5mm 90W: 12.600Lm 140Lm/W Ø264 x 172,5mm 100W: 14.000Lm 140Lm/W Ø383 x 193mm 120W: 16.800Lm 140Lm/W Ø383 x 193mm 150W: 21.000Lm 140Lm/W Ø383 x 193mm 200W: 28.000Lm 140Lm/W Ø383 x 203,5mm 240W: 33.600Lm 140Lm/W Ø383 x 203,5mm 300W: 42.000Lm 140Lm/W Ø383 x 257mm
Colour Rendering Index	73 (Optional 86)
Light Source	Nichia
Beam Angle	120° Optional 50° & 90°
Driver	Meanwell
Dimmable	0-10V dimmable driver (Optional)
Power Factor	>0,95
Voltage/ current	100-277V 50/60Hz
IP-code	IP65
Housing Material Aluminium	alloy + Toughened Glass
Operation Temperature	-30~+50°C
Lifetime	50.000 hours
Warranty	5 years
Weight	6-7kg
Certification	CE, CB, SAA, UL, DLC, ErP,RoHS

Available with sensor

70-300 Watt | 140Lm Lumen | 3000 4000 5000 Kelvin | IP 65 | 120

All transactions with LED Flatlight BV are subject to our general terms of trading, Copies are on request. All specifications are subject to change without notice.