

Downlight
 40,60,75W 145Lm/W 3000-6000K

Cotus





LED Flatlight: If you compare our LED Products to traditional lighting you will see that our lighting radiates less heat and has a much longer life span and a very low maintenance cost. Our products are made of quality parts and have a high energy saving level. We think quality is very important so we always make sure our products are tested and have the right certificates.

Applications: Supermarket, Store, Warehouse, Library, Museum, Office

Wattage	40, 60, 75W
Luminous Flux	145Lm/W
Kelvin	3000K, 4000K, 5000K, 6000K
Colour Rendering Index	>82, SDCM<4
Dimmable	Optional Dali/0-10V
Driver	Flicker free THD<15%
Installation	Pendant, Surface, Trackrail
Beam angle	2 x 45°
Power Factor	>0,95
UGR	>19
Voltage / Current	AC200-240V 50Hz/60Hz
IP-Code	IP20
Housing Material	Alu+ Lens (White lens optional)
Dimensions	40W: 584 x 125 x 13mm 60W: 1164 x 125 x 13mm 75W: 1454 x 125 x 13mm
Operation Temperature	-25~ +40°C
Lifetime	35.000h
Warranty	3 Years (5 Years optional)
Certification	CE, RoHS



40,60,75 Watt	145 Lm/W	3000- 6000 Kelvin	20 IPcode	2 x 45°
--------------------------	---------------------	----------------------------------	----------------------	----------------



All transactions with LED Flatlight BV are subject to our general terms of trading, Copies are on request. All specifications are subject to change without notice.