

Streetlight

15-150Watt 130Lm/W 150W: 125Lm/W





Rilux



LED Flatlight: If you compare our LED Products to traditional lighting you will see that our lighting radiates less heat and has a much longer life span and a very low maintenance cost. Our products are made of quality parts and have a high energy saving level. We think quality is very important so we always make sure our products are tested and have the right certificates.

Applications: Street, Parking

Wattage	15W 20W 30W 50W 70W 90W 120W 150W
Luminous Flux	130Lm/Watt (150W: 125Lm/W)
Kelvin	3000K/4000/5000K
Colour Rendering Index	>70
Beam angle	125°
Dimmable	Dali
Sensor	Daylight sensor, 5step timing, Photocell
Driver	Included
Power Factor	>0,9
Voltage / Current	100-277V 50~60Hz
IP-Code	IP66 IK08
Housing Material	Aluminum alloy + Class I
Dimensions	763 x 352 x 167mm
Operation Temperature	-40 + 50°C
Lifetime	50.000h
Warranty	5 Years
Certification	CE, RoHS, ENCE, CB, EMC, SAA, SASO, cULus



All transactions with LED Flatlight BV are subject to our general terms of trading, Copies are on request. All specifications are subject to change without notice.

SPECIAL PROJECTS | INDUSTRIAL | INTERIOR | SIGNING | UTILITY | RETAIL