

Utra thin Downlight 15W 1425-1587Lm 3000-5000K

Item: See below

Finko



LED Flatlight: If you compare our LED Products to traditional lighting you will see that our lighting radiates less heat and has a much longer life span and a very low maintenance cost. Our products are made of quality parts and have a high energy saving level. We think quality is very important so we always make sure our products are tested and have the right certificates.

Applications: Bathroom, Corridor, Shopping Center, Hotel, etc.

 Wattage
 12W 15W

 Luminous Flux
 1425-1587Lm

 Kelvin
 3000K 4000K

Colour Rendering Index>80Light Source2835 SMDBeam angle120°

Emergency Optional (3h Emergency)

Sensor Optional Power Factor >0,9

Voltage / Current 220-240V 50~60Hz

Material Black or White PC with Opal (RVS Ring Optional)

IP-Code IP54

Dimensions Ø 250 x 48mm

Operation Temperature -20 + 45°C

Lifetime 45.000h

Warranty 3 Years

Certification CE. RoHS













Item:

1002456

1002455

1002965	Downlight 'Finko' Black 12W 3000K
1002947	Downlight 'Finko' Grey 15W 3000K Dim Sensor
1002946	Downlight 'Finko' Grey 12W 3000K Sensor & EPS
1002945	Downlight 'Finko' Grey 12W 3000K Sensor On/off
1002944	Downlight 'Finko' Grey 12W 3000K EPS
1002943	Downlight 'Finko' Grey 12W 3000K
1002831	Downlight 'Finko' White 12W 4000K On/off Sensor EPS
1002824	Remote for 'Finko' White 15W 3000K Dim Sensor
1002823	Downlight 'Finko' White 15W 3000K Dim Sensor EPS
1002822	Downlight 'Finko' White 15W 3000K Dim Sensor
1002784	RVS ring t.b.v. Downlight 'Finko'
1002458	Downlight 'Finko' White 12W 3000K On/offSensor EPS
1002457	Downlight 'Finko' White 12W 3000K On/off Sensor

Downlight 'Finko' White 12W 3000K EPS

Downlight 'Finko' White 12W 3000K





All transactions with LED Flatlight BV are subject to our general terms of trading, Copies are on request. All specifications are subject to change without notice.