

PE IP69K Light  
20,36,45W 4000K 100Lm/W



# PE TRI-Proof



Unique patent design, TUV-GS, UL, DLC, IP69K, IK10, CE/ROHS certified, Available with PP and PC material, Water-proof, Dust-proof, Damp-proof, High borosilicate glass material support anti-corrosion, Excellent transmission of light and thermal conductivity, Energy saving up to 80%, And its flicker free.

Applications: Industry, Parking, Airport, Gas station/Carwash

|                        |  |
|------------------------|--|
| Wattage                | 20W 36W 45W  |
| Luminous Flux          | 100Lm/W  |
| Kelvin                 | 4000K  |
| Colour Rendering Index | >80  |
| Beam Angle             | 120°   |
| Dimmable Optional      | Optional, 0-10v Dimmable, Dali   |
| SDCM                   | <4   |
| Voltage/ current       | 200-240V   |
| IP-code                | IP69K  |
| DC Output              | 34~40V   |
| Housing Material       | Fixture PE IP69K Clips + Caps 316SS                                    |
| Dimensions             | 20W: 600mm x Ø74,5mm<br>36W: 1200mm x Ø74,5mm<br>45W: 1500mm x Ø74,5mm |
| Operation Temperature  | -20~+50 °C   |
| Lifetime               | 70.000 hours   |
| Warranty               | 5 years  |
| Certification          | CE, RoHS   |



All transactions with LED Flatlight BV are subject to our general terms of trading, Copies are on request. All specifications are subject to change without notice.